



syntha pulvin

## **TO WHOM IT MAY CONCERN**

### **BARLEY CHALU COATING THICKNESSES – MARINE GRADE STANDARD**


Following extensive testing and inspection of coating records at Barley Chalu, we can confirm that all materials are coated to a Minimum Film Thickness of 60 Microns and that any items not conforming to this requirement are rejected and reprocessed.

Therefore we confirm that Barley Chalu meet the Film Thickness requirement of both the Standard Syntha Pulvin Guarantee and the Syntha Pulvin Guarantee for Hazardous (Marine, Industrial or Swimming Pool) environments on all materials coated as part of their standard offer.

The Guarantee offer for Hazardous environments will still require confirmation from Valspar Powder Coatings Limited and the extra stipulations of

- Only SYNTHA PULVIN matt or matt metallic may be used
- All joints to be sealed with an approved mastic
- Exposed bare metal edges should be avoided
- Fully corroborative documented records showing cleaning periods not exceeding 3 months must be kept

Would still apply.



*Chris Mansfield*

**CHRIS MANSFIELD**  
ARCHITECTURAL BUSINESS MANAGER

Valspar Powder Coatings Limited  
95 Aston Church Road  
Birmingham B7 5RQ  
Tel: 0121 322 6900 Fax: 0121 322 6902

[www.synthapulvin.co.uk](http://www.synthapulvin.co.uk)